



Grapples

For wood, iron, rock, hay, concrete, solid manure, it's strong grip allows it to be used for moving multiple materials. Available in 30, 40, 49 and 52 inch openings.

Log Loaders



Technical Specifications for Jolex Grapples

GRAPPLE MODELS	G30	G40	G49	G52
Weight (lbs)	100	140	220	260
Maximum operation pression (psi)	2 300	2 300	2 300	2 300
Maximum grip force (lbs)	800	1 400	1 800	2 300
Opening Time (sec.) (3.5 gpm)	2.5	3	4.5	6
Closing time (sec.) (3.5 gpm)	3	4	6	8
Maximum closing (pcs)	3	3	3.5	4
Opening (pcs)	30	40	49	52
Charge Capacity (cubic inch)	18.5	34	47	53
Maximum lift weight (lbs)	2 150	3 950	5 400	6 900

Note: Jolex reserves the right to make changes without notice.



THE RELIABILITY YOU NEED.

Head Office: 171, boul. Labbe Nord, porte 1, Victoriaville (Quebec) G6P 1A7 Canada
 Phone: 819 758-4405 • Toll-Free: 1 888 369-8777 • E-mail: info@jolexmachinerie.com

Jolexmachinerie.com



Loaders



Grapples



Trailers

Loaders

Jolex log loaders are made with top quality materials to ensure great durability.

Features

- Available with or without booster seat
- Adapts to most machinery; tractor, trailer, truck, ATV, etc...
- Hardened steel axle rods
- Long reach on the axles for greater strength
- Tested steel structure
- 4000 psi hoses with very wear-resistant protective sheath and treated to resist UV rays

- Very manageable boom, it lifts almost parallel to the support post for more accessibility in tight places. It folds in on itself very close to its base for easy front loading.
- 360° rotation
- The Joystick type control system is adjustable in height.
- The clamp is continuously rotating.
- The grapple has a lot of clamping force, it can be used for wood, stone, hay, manure, iron, etc. It's design makes it possible to place the mingled wood properly.

Technical Specifications for Jolex Loaders

DESCRIPTION	DL950	DL1050	DL1200	DL1400	DL1650
Boom height	54"	63"	55"	72"	82"
Boom rotation	360°	360°	360°	360°	360°
Telescopic boom	20"	20"	24"	30"	48"
Total weight (lbs)	695	1 365	1 425	1 950	2 965
Maximum reach with clamp	9' 6"	10' 9"	12'	14'	16' 6"
Maximum reach with shovel	10' 6"	11' 9"	13'	15'	17' 6"
Minimum boom span	43"	31"	31"	31"	31"
Breakout force (lbs)	1 800	4 000	4 500	5 500	5 500
Digging depth (pds)	5'	6'	7'	8'	9.5'
Lift capacity at max. (lbs)	800	1 075	1 350	1 425	1 885
Lift capacity (lbs)	(6') 1 400	(7') 2 200	(8') 3 000	(8.5') 4 000	(9') 5 000
Grapple opening	30"	40"	40"	49"	52"
Grapple closing	3"	3"	3"	3.5"	4"
Grapple rotation	continuous	continuous	continuous	continuous	continuous
Excavation bucket	12"	14"	16"	18"	18"
Gravel bucket	20"	24"	24"	30"	30"
Working pressure (psi)	2 300	2 300	2 300	2 300	2 300
Recommended oil flow (gpm)	1.5 to 3	4 to 8	5 to 10	6 to 12	8 to 15
Recommended Tractor Force (hp)	20 to 45	35 to 70	45 to 90	55 to 120	90 +

Note: Jolex reserves the right to make changes without notice.

Trailers

Several options available: round bale platform, winch, pivoting pole, adjustable tandem, pivoting tandem, controlled wheels, etc... They adapt to all your needs!

Wheel driven trailer

Trailer equipped with a system of driven wheels allowing to work faster and safer. Convenient for crossing hard-to-reach places or holding the trailer on a descent. Ideal for ATV or mini tractor.

*Available on RM811 and RM1011 models.

Dump Trailer

Designed on a reinforced frame, the trailer is solid and practical. Available in different sizes.



DL1650

Technical Specifications for Jolex Trailers

MODEL	RM811	RM1011	RM1212	RM1416
Total length	12' 7"	15' 8"	18'	19' 11"
Total width	61"	69"	81"	87"
Loading height	18"	25,25"	29"	33,75"
Loading length	8'	10'	12'	14'
Total trailer weight (lbs)	665	1 210	2 055	2 550
Load capacity (lbs)	5 000	10 000	15 000	20 000
Axles Diameter	2"	2 1/2"	2 1/2"	2 3/4"
Tire diameter	11L15 8 ply	11L15 8 ply	12.5L15 12 ply	16.5L16.1 14 ply
Maximum number of posts For loader	8 DL950	8 DL1200 DL1050	12 DL1400	12 DL1650 DL1400

Note: Jolex reserves the right to make changes without notice.



360°

« The one and only on the market that rotates 360 degrees! »



DL1400



DL950



DL1400